

131B0042

FC-302P7K5T5E20H1XGXXXXSXXXXAXBXCXXXXDX

Frequency converter
FC-302P7K5T5E20H1XGXXXXSXXXXAXBXCXXXXDX
VLT® AutomationDrive FC-302
(P7K5) 7.5 KW / 10 HP,
Three phase, 380 - 500 VAC, (E20) IP20 / Chassis
(H1) RFI Class A1/B (C1)
No brake chopper
Graphical Loc. Cont. Panel
Not coated PCB, No Mains Option
Latest release std. SW.
Frame: A3
No A Option, No B Option
No C1 option, No D option

Other options according to Model code

Model code: FC-302P7K5T5E20H1XGXXXXSXXXXAXBXCXXXXDX

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

View Efficiency Data

PRODUCT DETAILS

Gross weight		7.546 Kilogram
Net weight		6.54 Kilogram
Volume		27.246 Liter
EAN		5702427094352
Product View (Switch)	GLBL	Global (Standard)
Product Group	FC-	VLT® AutomationDrive FC-
Series	302	302
Power Rating	P7K5	(P7K5) 7.5 KW / 10 HP
Phase	T	Three phase
Mains Voltage	5	380 - 500 VAC
Enclosure	E20	(E20) IP20 / Chassis
RFI Filter	H1	(H1) RFI Class A1/B (C1)
Brake - Safe Stop	X	No brake chopper
LCP	G	Graphical Loc. Cont. Panel
Coating PCB	X	Not coated PCB
Mains Option	X	No Mains Option
Adaptation A	X	Standard Cable Entries
Adaptation B	X	No adaptation
Software Release	SXXX	Latest release std. SW.
Software Language Pack	X	Standard Language Pack
A Option	AX	No A Option
B Option	BX	No B Option
C0 Option MCO	CX	No C0 option
C1 Option	X	No C1 option

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

C Option Software	XX	No software option
D Option	DX	No D option
Frame Size	A3	A3
Typecode Part 1		FC-302P7K5T5E20H1XGX
Typecode Part 2		XXXSXXXXAXBXCXXXXDX
Product Catalog	NO_VIEW	NO VIEW
Power 160% (HO) [KW]	7.5	7.5
Height [mm]	268,0	268,0
Width w/ no C options [mm]	130,0	130,0
Width w/ two C options [mm]	190,0	190,0
Depth [mm]	205,0	205,0
Depth with Option A/B [mm]	220,0	220,0
kVA	11.1	11.1
Power Loss HO [W]	225	225
Power Loss HO [W]	225	225
Continuous Current (HO) [A]	16	16
Intermittent Current (HO) [A]	25.6	25.6
Continuous Current (HO) [A]	14.5	14.5
Intermittent Current (HO) [A]	23.2	23.2
Calculated Gross Weight [kg]		7.546
Calculated Net Weight [kg]		6.54
ECCN EU	Y901	Y901
ECCN US	3A999.a	3A999.a
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Modelcode01		FC-302P7K5T5E20H1XGX
Modelcode02		XXXSXXXXAXBXCXXXXDX
Recommended Plant	ERR01	ERR01

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.